

TORQUE CONTROL SYSTEMS

DRILLS

ASSEMBLY

ABRASIVE

FINISHING

PERCUSSIVE

SPECIALTY

ACCESSORIES



TC50A

Torque Control System

Model Number	Tool Supply Hose Size	Height		Width		Depth		Weight		Power Req.
		in.	mm	in.	mm	in.	mm	lb	kg	
TC50A	3/8" - 1/2"	12	305	8	203	6	152	10	4.0	100V-240V
TC50A-2	1/2" - 3/4"	12	305	8.0	203	6	152	10	4.0	100V-240V
TC-6A	1/2", 3/4"	10.3	260	18.3	463	12.5	317	40	18.4	110V

Standard Equipment TC-6A:
 1/2 or 3/4 inch NPT piping
 Programmable FFC-3 processor
 Internal pressure regulator valve
 Electronic sensor valve
 Normally-open solenoid valve
 Built-in Red/Green warning signal
 Built-in External exhaust muffler
 Heavy-duty enclosure w/lockable, access door
 External channel selector switch
 External, lockable on/off switch
 10 ft grounded power cord

Accessories:
 Controller Accessories, see page 62

Optional Chips:
 10039-Used with Non-shutoff Pulse and Impact tools
 10041-Used with Stall Drive tools
 10045-Used in 2-step applications with Non-shutoff Pulse and Impact tools
 10066-Closed Loop System (Used with Transducerized tools)

